

SECURITY DESIGNED WITH YOU IN MIND

BLU-IO21



Azure Access Technology BLU-IO21 Downstream Input/Output Board (2 Supervised Inputs & 1 Outputs)

The BLU-IO21 is a downstream, serial device that brings door monitoring & control I/O to the door. It has supervised inputs for door contact & enter/exit actuators, and relay output for the door strike. The IO21 comes in a labeled enclosure allowing for installation anywhere. The IO21 can be installed on the same RS485 bus as OSDP readers. When used with controllers utilizing extended reader licenses, the IO21 quickly reduces cost-per-door.



SECURITY

OSDP

AES 128/256

Encrypted Firmware

REGULATORY

UL 294, UL294B, UL1076, UL2610
(Hardware)

ULC/ORD C1076

CE Compliant

FCC Part 15 Class A

RoHS

FEATURES

- ❑ **FULLY ENCRYPTED COMMUNICATIONS**
 - > Serial communication to Azure Intelligent Controllers (ICs) are secure.
- ❑ **2 FLEXIBLE ALARM INPUTS**
 - > Supervised or Unsupervised
 - > Supports pre-defined standards and custom input-supervision values
- ❑ **1 RELAY OUTPUTS**
 - > Configurable pulse/activation times
- ❑ **LED STATUS & DIAGNOSTICS**
 - > LEDs for all onboard activity and hardware interface statuses
 - > Visual diagnostics via LEDs
- ❑ **DOOR MONITORING & CONTROL AT THE "EDGE"**
 - > Ability to multi-drop BLU-IO21 devices on same RS485 bus as OSDP readers for minimal wiring to the door
 - > Custom enclosure, with all connections labeled, allows installation at the door or anywhere
 - > Can share power with 12VDC readers



MAVIN
TECHNOLOGIES

12 Aqueduct Street, 3rd floor
Rochester, New York 14614
866 680.8346
info@go-mavin.com

go-mavin.com

MAVIN SECURITY MANAGEMENT PLATFORM



INPUT POWER

- 12 VDC; 28mA Max current

GENERAL INFORMATION

- INDUSTRIAL operation and storage temperature (-40°C to +85°C)
- 5% to 95% humidity
- PCB Dimensions: 1.88 in (47.75mm) x 1.9in (48.26mm) x 0.53in (13.46mm)
- Enclosure Dimensions (including flanges): 2.16 in (54.86mm) x 3.35in (85.19mm) x 0.77in (19.56mm)
- PCB Weight: 0.038 pounds (17.24 grams)
- PCB + Enclosure Weight: 0.086 pounds (39 grams)

ONBOARD HARDWARE INTERFACES

- 2 Configurable Supervised/Unsupervised Inputs
- 1 Form-C Relay Outputs
 - > 2A @ 30VDC MAX rating
- 2 Pushbuttons for Configuration Menus
- 1 Upstream RS485 Comm Port
 - > 9,600 to 115,200 baud
 - > 2-wire interface supported

FEATURES

- **HIGH-PRECISION ALARM INPUTS**
 - > Supervised Input circuitry is designed with application-specific components to maintain stability and reliability in even the most extreme conditions
 - > A combination of Software and Hardware filtering suppresses noise and eliminates false alarms
- **ENERGY EFFICIENT**
 - > Low power consumption compared to other panels with similar hardware interfaces
- **REDUCED COST PER DOOR**
 - > Installations of controllers using expanded reader licenses can utilize the IO21 to provide IO for door monitoring and control beyond the number of IO connections natively on the controller
- **OSDP**
 - > Supports OSDP communication
 - > OSDP serial configuration set with pushbuttons or software commands

SYSTEM DIAGRAM

